

Configurations

Models in detail

- ✓ Standard
- Option
- ✗ unavailable



CTM CTM RL



CTM F CTM F RL



CTM P CTM P RL



CTM PF CTM PF RL



TwinTower CTM + CTM RL
(see Page 13)

Models in detail

Electrical connection

380–415 volt | 50–60 Hz | 16 amp | 3 phase
 220–240 volt | 50–60 Hz | 32 amp | 1 phase
 220–240 volt | 50–60 Hz | 16 amp | 1 phase*

*Reduction in performance for milk-based beverages –45%

Output

5800-7100W

Dimensions (W/D/H)

Coffee machine with refrigerator

Manually adjustable coffee output 85 – 172 mm

Automatic coffee output 96 – 192 mm

Weight

Volume 70 dB

1 grinder

2 grinders

Outer material Alunox

Special colors (acc. to RAL code)

Feet 57 mm

Feet 77 mm

Foot skirting 57 mm

Foot skirting 77 mm

Bean hopper ~1.7 kg

Powder unit 2 kg

Syrup flavors 1–4

Lockable container (beans, powder, refrigerator, grounds tray)

Grounds chute

Fixed water supply

Tank operation

Cold milk / cold milk foam

Payment system connection

2 types of milk

ThermoplanConnect telemetry system (Remote update)

ISQ (Intelligent Shot Quality)

LatteArtist

Language software (see Page 23)

✓

○

○

✓

320x600x646 mm

600x600x646 mm

✓

○

60/80 kg

✓

✓

○

✓

○

✓

○

○

✗

✓

✗

○

○

○

✓

✗

✓

○

○

○

✓

○

✓

○

○

✓

488x600x646 mm

768x600x646 mm

✓

○

70/90 kg

✓

✓

○

✓

○

✓

○

○

✗

✓

✗

○

○

○

✓

✗

✓

○

○

○

✓

○

✓

○

○

✓

412x600x646 mm

692x600x646 mm

✓

○

70/90 kg

✓

✓

○

✓

○

✓

○

○

✗

✓

✓

✗

○

○

✓

✗

✓

○

○

○

✓

○

✓

○

○

✓

580x600x646 mm

860x600x646 mm

✓

○

80/105 kg

✓

✓

○

✓

○

✓

○

○

✗

✓

✓

○

○

○

✓

✗

✓

○

○

○

✓

○

✓

○

○

✓

920x600x646 mm

✓

○

140 kg

✓

✓

○

✓

○

✓

○

○

✗

✓

○

○

○

○

✓

✗

✓

○

○

○

✓

○